



GALAXY "GX"



For illustrative purposes only

ENGINE

Engine brand	DEUTZ
Engine model	F4M2011
Cylinders	4
Speed	1500 r.p.m.
Cubic capacity	3.11 l
Air intake	Aspirated
Standard voltage	12 Vdc
Optional voltage	24 Vdc
Sae	3-11½
BMEP	750 kPa
Cooling	Oil
Flywheel P.R.P. Power	28.0 kW
Flywheel Stand-by Power	29.4 kW
Fuel Cons. at 100% (L.T.P.)	7.7 l/h
Fuel Cons. at 100% (P.R.P.)	7.2 l/h
Fuel Cons. at 75% (P.R.P.)	5.5 l/h
Fuel Cons. at 50% (P.R.P.)	4.2 l/h
Fuel Cons. at 25% (P.R.P.)	3.1 l/h
Electronic regulator	On request
Precision class	G2
Oil quantity	13.0 l
Engine Antifreeze capacity	0.0 l
Radiator standard	ROA
Heat from radiator	17.0 kW
Heat from exhaust	25.0 kW
Heat from radiation	0.0 kW
Exhaust temperature	600 °C
Cooling air flow	30.00 m³/min
Combustion air flow	0.00 m³/min
Exhaust gas flow	5.54 m³/min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Stage 2

MAIN DATA

Continuous power (PRP)	30.0 (kVA)
Continuous power (PRP)	24.0 (kW)
Stand-by power (LTP)	33.0 (kVA)
Stand-by power (LTP)	26.4 (kW)
Voltage • Frequency • Power Factor	400V • 50Hz • 0.8 cosφ
Sound pressure 7 m.	60.0 dBA

DIMENSIONS AND WEIGHT

Width	910 mm
Length	2000 mm
Height	1600 mm
Weight	1000 kg

ALTERNATOR

Alternator brand	STAMFORD
Alternator model	PI144G
P.R.P. Power	30.0 kVA
L.T.P. Power	33.0 kVA
Connection	Series star
Phases	3PH+N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS480
Precision	1.0 ± %

BASEFRAME

Model	GV020HD
Standard tank	120 l
Optional tank	50 l
Oversized tank*	0 l

CANOPY & SILENCER

Canopy model	GV020
Silencer model	MSR/a 50
Silencer outlet diameter	60.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

